

LOCATE 1ST CLIP 12" MAX FROM EAVE  
OR PER ATTACHMENT SCHEDULE

SELECT SEAM PANEL

SEAM COVER

1/8" RIVETS  
BOTH SIDES

**DESIGN CAUTION:**  
ROOF SLOPE TRANSITIONS  
SUCH AS FASCIAS MAY ESTABLISH AN  
UNWANTED POINT OF PANEL FIXITY.

FIELD CUT MALE AND FEMALE  
LEGS OF PANEL AND BEND  
OVER EDGE. SEAL ENDS  
OF PANEL RIBS BEFORE  
INSTALLING SEAM COVER

SELECT SEAM PANEL

30# FELT  
(NOT BY AEP-SPAN)

SUBSTRATE

LOCATE 1ST CLIP 12" MAX FROM EAVE  
OR PER ATTACHMENT SCHEDULE

PANCAKE HEAD  
FASTENERS

1/4" MIN. CLEARANCE  
FOR WEEPAGE

FIELD NOTCH  
AND HEM 1"

DRIP FLASHING

SHOULD BE MINIMUM 1/4" GREATER  
THAN PANEL HEIGHT.



## DESIGN SPAN HP & SELECT SEAM

FASCIA TRANSITION

DS-04