

FIELD NOTCH
ZEE CLOSURE
AT RIB

NON-SKINNING BUTYL
SEALANT APPLIED TO
ENDS OF ZEE CLOSURE

INSTALLATION NOTE:
CLOSE HEM OF PANELS
WITH DUCK BILLS TO
ALLOW NOTCHED ZEE
CLOSURE TO FIT
TIGHTLY TO PANEL

SECTION X-X

3/16"x7/8" BUTYL TAPE

18 GA. CONT.
PANEL END
SUPPORT

RIDGE/HIP COVER

3/16"x7/8"
CONT. BUTYL TAPE

1/4-14 X 7/8" HWH SCOTS
W/NEO. WASHER PAINTED
@ RIBS AND MIN. (1)
BETWEEN RIBS OR
MAX. 9" CTRS.

HAND CRIMP
10"

HWH FASTENER
RIDGE: (4) PER PANEL
HIP: @ 4" O.C.

"Z" CLOSURE
FIELD CUT TO FIT
TIGHTLY BETWEEN RIBS

3/16"x7/8"
CONT. BUTYL TAPE

NON-SKINNING BUTYL
SEALANT@ ENDS OF ZEE



SPAN-LOK hp



RIDGE/HIP - FLOATING

SLHP-15