


NON-SKINNING BUTYL
SEALANT APPLIED TO
ENDS OF ZEE CLOSURE

FIELD NOTCH
ZEE CLOSURE
AT RIB



INSTALLATION NOTE:
CLOSE HEM OF PANELS
WITH DUCK BILLS TO
ALLOW NOTCHED ZEE
CLOSURE TO FIT
TIGHTLY TO PANEL

SECTION X-X

3/16"x7/8" BUTYL TAPE


18 GA. CONT. PANEL
END SUPPORT (SL2ES2)

RIDGE/HIP COVER**
(RH168: 10")
(RH170: 12")

3/16"x7/8"
CONT. BUTYL TAPE

1/4-14 X 7/8" HWH
W/NEO. WASHER PAINTED
@ RIBS AND MIN. (1)
BETWEEN RIBS OR
MAX. 9" CTRS.

90° HAND CRIMP
10"



HWH FASTENER
RIDGE: (4) PER PANEL
HIP: @ 4" O.C.

"Z" CLOSURE (ZC223)
FIELD CUT TO FIT
TIGHTLY BETWEEN RIBS

3/16"x7/8"
CONT. BUTYL TAPE

NON-SKINNING BUTYL
SEALANT @ ENDS OF ZEE



SPAN-LOK

RIDGE/HIP - FLOATING

SL-11