

FIELD NOTCH  
ZEE CLOSURE  
AT RIB

NON-SKINNING BUTYL  
SEALANT APPLIED TO  
ENDS OF ZEE CLOSURE

INSTALLATION NOTE:  
CLOSE HEM OF PANELS  
WITH DUCK BILLS TO  
ALLOW NOTCHED ZEE  
CLOSURE TO FIT  
TIGHTLY TO PANEL

SECTION X-X

3/16"x7/8" BUTYL TAPE

18 GA. CONT.  
PANEL END  
SUPPORT

RIDGE/HIP COVER

3/16"x7/8"  
CONT. BUTYL TAPE

1/4-14 X 7/8" HWH SCOTS  
W/NEO. WASHER PAINTED  
@ RIBS AND MIN. (1)  
BETWEEN RIBS OR  
MAX. 9" CTRS.

HAND CRIMP  
10"

HWH FASTENER  
RIDGE: (4) PER PANEL  
HIP: @ 4" O.C.

"Z" CLOSURE  
FIELD CUT TO FIT  
TIGHTLY BETWEEN RIBS

3/16"x7/8"  
CONT. BUTYL TAPE

NON-SKINNING BUTYL  
SEALANT@ ENDS OF ZEE



SPAN-LOK

RIDGE/HIP - FLOATING

SL-15