

FIELD NOTCH
ZEE CLOSURE
AT RIB

NON-SKINNING BUTYL
SEALANT APPLIED TO
ENDS OF ZEE CLOSURE

INSTALLATION NOTE:
CLOSE HEM OF PANELS
WITH DUCK BILLS TO
ALLOW NOTCHED ZEE
CLOSURE TO FIT
TIGHTLY TO PANEL

SECTION X-X

3/16"x7/8" BUTYL TAPE

CONSTRUCTION SEALANT
(NOT BY AEP-SPAN)

CONTINUOUS 3/8" BEAD
NON-SKINNING BUTYL SEALANT

REGLET FLASHING

HEAD WALL FLASHING

ENGINEERED
FASTENER
(NOT BY AEP-SPAN)

180° SEAM W/ELECTRIC
SEAMER *

90° HAND CRIMP
10"

1/8" POP RIVETS
@12" O.C.

3/16"x7/8"
BUTYL TAPE

ZEE CLOSURE

NON-SKINNING BUTYL SEALANT
APPLIED TO ENDS OF ZEE
CLOSURE

16 GA. PANEL SUPPORT
(NOT REQ'D W/LOW PROFILE CLIP)

FASTENER AS REQUIRED

3/16"x7/8" CONT. BUTYL TAPE

FASTENER AS REQUIRED

* - FIRST 10" OF PANEL DOWNHILL OF HEAD WALL FLASHING WILL
NEED TO BE 180° HAND CRIMPED TO GET SEAMER ON/OFF



SPANSEAM



HEAD WALL - FIXED

SPS-10